






To ensure you get the best from the product supplied to you, we advise you follow the care instructions within this datasheet.

Fabric	<b>Flame Retardancy</b>	NDFR
	<b>Fire Certification</b>	BS5867, M1, B1, EN13773
	<b>Brand Name (and Manufacturer)</b>	J&C Joel Ltd.
	<b>Material (Blending Ratio)</b>	100% Cotton
	<b>Construction of Fabric</b>	Plain Weave
Chemicals	<b>Surface Treatments</b>	Scour, Desize, Dye & Flame Retard
	<b>Brand Name of Flame Retardant Chemicals</b>	KAPP, Chemie GMBH & Co KG
	<b>Chemical name of Flame Retardant Chemicals</b>	Kappaflam CFP
	<b>Process of Flame Retardant Chemicals</b>	Immersion
Care	<b>Information</b>	<p>Non-Durably Flame Retardant. This means that the fabric is chemically treated and if wet (in any way) should be retreated to meet the flammability requirements of BS5867 Part 2 Type B, M1, B1 and EN13773. Therefore, the cloth will not withstand wet cleaning and should be re-flame proofed whenever wet. The cloth can be professionally dry cleaned using the correct chemical process.</p> <p>Notwithstanding the aforementioned, it would be our advice to only dry clean this material periodically. We would suggest that the curtain be soft-brushed on a regular basis and periodically cleaned using a vacuum and drapery attachment. Commercial flame retardants may alter the aesthetics, appearance, colour or performance of the textile material.</p> <p>This fabric is not pre-shrunk.</p>
	<b>Laundering Treatment</b>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Dry Clean Only</p> </div> <div style="text-align: center;">  <p>Do Not Wash</p> </div> <div style="text-align: center;">  <p>Do Not Bleach</p> </div> <div style="text-align: center;">  <p>Do Not Iron</p> </div> <div style="text-align: center;">  <p>Do Not Tumble Dry</p> </div> </div>
<b>Notes</b>		



Fire Rating:  
NDFR



Approx Bale Length:  
60m / 197ft



Width:  
720cm / 283"



Weight:  
270 g/m<sup>2</sup>



Fire Certification:  
BS5867, M1, B1,  
EN13773



Colours  
Available

For further information please contact our sales team [sales@jcjoel.com](mailto:sales@jcjoel.com)