








To ensure you get the best from the product supplied to you, we advise you follow the care instructions within this datasheet.


Fabric	Flame Retardancy	NDFR
	Fire Certification	BS5867, M1, B1, NFPA 701, AS 1530.2 /3
	Brand Name (and Manufacturer)	J&C Joel Ltd.
	Material (Blending Ratio)	100% Cotton
	Construction of Fabric	Knitted
Chemicals	Surface Treatments	Dyed, Chemically Treated
	Brand Name of Flame Retardant Chemicals	Thor
	Chemical name of Flame Retardant Chemicals	Aflammit, KRE
	Process of Flame Retardant Chemicals	Immersion
Care	Information	<p>Non-Durably Flame Retardant. This means that the fabric is chemically treated and if wet (in any way) should be retreated to meet the flammability requirements of BS5867 Part 2 Type B, M1, B1, NFPA 701 and AS 1530.2 /3. Therefore, the cloth will not withstand wet cleaning and should be re-flame proofed whenever wet. The cloth can be professionally dry cleaned using the correct chemical process.</p> <p>Notwithstanding the aforementioned, it would be our advice to only dry clean this material periodically. We would suggest that the curtain be soft-brushed on a regular basis and periodically cleaned using a vacuum and drapery attachment. Commercial flame retardants may alter the aesthetics, appearance, colour or performance of the textile material.</p> <p>This fabric is not pre-shrunk.</p>
	Laundering Treatment	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Dry Clean Only</p> </div> <div style="text-align: center;">  <p>Do Not Wash</p> </div> <div style="text-align: center;">  <p>Do Not Bleach</p> </div> <div style="text-align: center;">  <p>Do Not Iron</p> </div> <div style="text-align: center;">  <p>Do Not Tumble Dry</p> </div> </div>
Notes		




Fire Rating:
NDFR




Approx Bale Length:
58m / 190ft




Width:
360cm / 142"



Weight:
100 g/m²



Fire Certification:
BS5867, M1, B1,
NFPA 701, AS 1530.2 /3



Colour
Available

For further information please contact our sales team sales@jcjoel.com