

IFR Molton CS

Perfect for: Stage • Masking • Decorative/Scenic • Film & TV • Acoustics

J&C Joel TM
Inspiration in every performance

www.jcjoel.com

Composition and Care

300 cm 3

Fire Certificates

BS5867 Part 2 Type B 4

EN13501-1 8

TECHNICAL



NDFR
Non Durably Flame Retardant
chemically treated with a water solution and if wetted in any way should be retreated



DFR
Durably Flame Retardant
chemically treated to withstand a number of cleanings



IFR
Inherently Flame Retardant
woven from fibres with a high flame retardancy



FR
Flame Retardant
chemically treated to an individual specification



NOT FR
Not Flame Retardant no flame retardant treatment



Confirmation that the fabric meets one or more flame retardant standards

BS5867 BS5867 Pt2 B is the British Standard for flame retardant fabrics used for curtains and drapes

BS5852 BS5852 Pt1 is the British Standard for flammability of upholstered composites for seating

BS4790 BS4790: 1987 Determination of the effects of a small source of ignition on textile floor coverings hot metal nut method (method 1, loose laid)

EN13773: 2003 Meets European fire safety standards for vertically hung fabrics. Burning behavior, ignitability testing of curtain fabric for use in the contract market.

TL 1080-0002/8 German Military Specification for horizontally tested materials

EN14041 Details the requirement for CE Marking of textiles, laminate and resilient floor coverings

BS7905-1:2001 Lifting equipment for performance, broadcast and similar applications.

ATTRIBUTES



Approx roll length of material in linear metres (m) & feet (ft)



Approx width of material in centimetres (cm) & inches (")



Approx weight in grams per metre squared (g/m²)



Approx thickness in (mm)

M1, M2, M4 Conforms to French Fire Regulations

B1, B2 Conforms to German Fire Regulations DIN 4102

IMO Conforms to International Maritime Organisation regulations

Classe Uno Meets Italian Fire Regulations

BS EN13501-1 Fire Classification of construction, products and building elements. Classification using test data from reaction to fire tests

CFC EN ISO 9239-1 Reaction to fire test. Horizontal surface spread of flame on floor covering system. Determination of the burning behaviour using a retardant heat source

NFPA 701 NFPA 701: (USA) Standard Methods of Fire Tests for Flame Propagation of Textiles and Films

EN9239-1 Reaction to fire tests – horizontal surface spread of flame on floor covering systems

DIN EN1021 Meets European fire safety standards for exposure to different ignition sources, namely a lit cigarette and butane flame. Assessment of the ignitability of upholstered furniture



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

To ensure you get the best from the product supplied to you, we advise you follow the care instructions within this datasheet.

Fabric	Flame Retardancy	IFR
	Fire Certification	BS5867 Part 2 Type B, EN13501-1
	Brand Name (and Manufacturer)	J&C Joel Ltd.
	Material (Blending Ratio)	100% Polyester
	Construction of Fabric	Dyed
Chemicals	Surface Treatments	N/A
	Brand Name of Flame Retardant Chemicals	N/A
	Chemical name of Flame Retardant Chemicals	N/A
	Process of Flame Retardant Chemicals	N/A
Care	Information	Inherently Flame Retardant to BS5867 Part 2 Type B and EN13501-1. This means that the man-made fibres are flame retardant for life and if wet, would not need to be re-flameproofed. Therefore, the cloth will withstand wet cleaning but we would advise and suggest professional dry cleaning only, using the correct chemical process. Notwithstanding the aforementioned, it would be our advice to only dry clean this material periodically. We would suggest that the curtain be soft-brushed on a regular basis and periodically cleaned using a vacuum and drapery attachment. This fabric is not pre-shrunk.
	Laundering Treatment	     Dry Clean Only Do Not Wash Do Not Bleach Do Not Iron Do Not Tumble Dry
Notes		



Fire Rating:
IFR



Approx Roll Length:
60m / 197ft



Width:
300cm / 118"



Weight:
320 g/m²



Fire Certification:
BS5867 Part 2
Type B, EN13501-1



Colour
Available
2



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: BS5867 Part 2 Type B

J&C Joel 
Inspiration in every performance



Wira House, West Park Ring Road,
Leeds, LS16 6QL, UK.
Telephone: +44 (0)113 259 1999
Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 15 August 2017

Our Ref: 53651-S

Your Ref: -

Page: 1 of 4

Client: J. & C. Joel Limited
Corporation Mill
Corporation Street
Sowerby Bridge
Halifax
HX6 2QQ

Job Title: Surface Ignition Of Curtains & Drapes

Client's Order No: -

Date of Receipt: 16 June 2017

Date of Test Start: 29 June 2017

Description of Sample(s): One sample identified as follows was received for testing:
IFR Molton, stated to be IFR

Work Requested: We were asked to make the following test:
BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds



Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL.
A company registered in England & Wales with company number 04069653. VAT Number GB 806354805.
The supply of all goods and services is subject to our standard terms of business, copies of which are available on request.
Our laboratories are accredited to EN ISO/IEC 17025.

Copyright © 2017 Shirley Technologies Limited. All rights reserved.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: BS5867 Part 2 Type B

J&C Joel 
Inspiration in every performance



TESTING • CERTIFICATION • AUDITING

J. & C. Joel Limited

Sample was identified as follows:

IFR Molton, stated to be IFR

Wire House, West Park Ring Road,
Leeds, LS16 6QL, UK.
Telephone: +44 (0)113 259 1999
Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 15 August 2017

Our Ref: 53651-5

Your Ref: -

Page: 2 of 4

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Testing as received.

Three specimens from both length and width were tested in accordance with BS EN ISO 15025: Procedure A (surface ignition): 2002. The sample was tested at 20 °C and 60 % relative humidity (R.H.).

Each specimen was subjected to an applied flame using propane and a 15 second flame application time. The results obtained (shown in the table below) were assessed according to the requirements of BS 5867: Part 2: 2008 (2015).

Pre-treatment

If the fabric is a pass in the "as received" condition then the fabric is subjected a water soak procedure as specified in BS EN 1021: Annex D: 2006.

Testing after pre-treatment

Three specimens, after pre-treatment, from both length and width were tested following the procedure described above.

Test results relate only to the sample tested.

The results for all tests are given in the table(s) on the following page(s).

Reported by:
J Coleman
Fire Technician

Countersigned By:
P Doherty
Operational Head

Enquiries concerning this report should be addressed to Customer Services.



1066

Shirley® Technologies Limited. Registered Office: Wire House, West Park Ring Road, Leeds, LS16 6QL.
A company registered in England & Wales with company number 04660951. VAT Number GB 81674800.
The supply of all goods and services is subject to our standard terms of business, copies of which are available on request.
Our laboratories are accredited to EN ISO/IEC 17025.

Copyright © 2017 Shirley Technologies Limited. All rights reserved.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: BS5867 Part 2 Type B

J&C Joel 
Inspiration in every performance



TESTING • CERTIFICATION • AUDITING

J. & C. Joel Limited

RESULTS

Sample Ref: IFR Molton, stated to be IFR

Wira House, West Park Ring Road,
Leeds, LS16 6QL, UK.
Telephone: +44 (0)113 259 1999
Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 15 August 2017

Our Ref: 53651-5

Your Ref: -

Page: 3 of 4

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Testing as Received

Specimen No.	Length			Width		
	1	2	3	4	5	6
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No

Requirements

Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, if the second 6 specimens all pass the result is a pass.

Result in 'as received': Pass

Testing after pre-treatment

Specimen No.	Length			Width		
	1	2	3	4	5	6
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No

Requirements

Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, if the second 6 specimens all pass the result is a pass.

Result in 'after pre-treatment': Pass



1068

Shirley* Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL.
A company registered in England & Wales with company number 04660633. VNT Number GB 836764800.
The supply of all goods and services is subject to our standard terms of business, copies of which are available on request.
Our laboratories are accredited to EN ISO/IEC 17025.

Copyright © 2017 Shirley Technologies Limited. All rights reserved.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: BS5867 Part 2 Type B

J&C Joel 
Inspiration in every performance



Wira House, West Park Ring Road,
Leeds, LS16 6QL, UK.
Telephone: +44 (0)113 259 1999
Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 15 August 2017

Our Ref: 53651-5

Your Ref: -

Page: 4 of 4

J. & C. Joel Limited

Conclusion

The fabric meets the Type B performance requirements of BS 5867: Part 2: 2008 (2015).

This material should be identified with the manufacturers name, trademark or other identifying mark, the statement 'Flammability complies with the requirements of BS 5867: Part 2: Type B and instructions of any special precautions to be taken concerning care (including cleansing) of the curtain, drape or window blind to be manufactured from the fabric, preferably using an appropriate care labelling symbol in accordance with BS EN 23758 and taking account of the pre-treatment using in this test and the requirements of Clause 4 of BS 5867: Part 2: 2008 (2015). If the fabric is unsuitable for cleansing, this shall be stated.

Uncertainty Budget

There is no uncertainty budget associated with BS 5867: Part 2: Type B as no measurements are determined, the pass/fail criteria is assessed visually.

SPECIMEN



Shirley® Technologies Limited, Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL.
A company registered in England & Wales with company number 04601953, VAT Number GB 836164800.
The supply of all goods and services is subject to our standard terms of business, copies of which are available on request.
Our laboratories are accredited to EN ISO/IEC 17025.

Copyright © 2017 Shirley Technologies Limited. All rights reserved.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: EN13501-1

J&C Joel 
Inspiration in every performance

Prüfinstitut Hoch GmbH

Lerchenweg 1
D-97650 Fladungen
Tel.: 09778-7480-200
hoch.fladungen@t-online.de

www.brandverhalten.de



Prüfinstitut für das Brandverhalten von Bauprodukten,
Bauaufsichtlich anerkannte Prüf-, Überwachungs- und Zertifizierungsstelle

KB-Hoch-260095

KLASSIFIZIERUNGSBERICHT

Klassifizierung des Brandverhaltens nach EN 13501-1 ¹⁾

CLASSIFICATION REPORT

Reaction to fire classification according to EN 13501-1 ¹⁾

Auftraggeber
Client

Herstellwerk
Production site

Gegenstand
Subject "CS Molton"

Beschreibung
Description Molton Gewebe in den Farben schwarz oder weiß.
Molton fabric in black or white.

Klassifizierung
Classification **B – s1,d0**

Berichtsdatum
Issue date 26.01.2026

Geltungsdauer
Validity 31.01.2031 ²⁾ (siehe Abschnitt 5.1 / confer to section 5.1)

Dieser Bericht umfasst 5 Seiten und darf nicht auszugsweise benutzt oder veröffentlicht werden. Für rechtliche Belange ist ausschließlich der deutsche Wortlaut maßgebend.
The report comprises 5 pages and must not be used or reproduced partially or in extracts. For legal interests, only the German wording is decisive.

¹⁾ EN 13501-1:2018

²⁾ Verlängerung auf Antrag / Prolongation on request

Mitglied der 
notified body: 1508

Durch die DAkkS nach DIN EN ISO/IEC 17025 akkreditiertes Prüflaboratorium.
Die Akkreditierung gilt für die in der Urkunde aufgeführten Prüfverfahren.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: EN13501-1

J&C Joel 
Inspiration in every performance



Prüfinstitut Hoch GmbH
Lerchenweg 1
D-97650 Fladungen

Seite 2 von 5 des Klassifizierungsberichts
page 2 of 5 of classification report
KB-Hoch-260095

1. Einführung / Introduction

Dieser Klassifizierungsbericht zum Brandverhalten definiert die Klassifizierung, die dem Bauprodukt in Übereinstimmung mit den Verfahren nach EN 13501-1:2018 zugeordnet wird.

This classification report defines the classification assigned to the construction product in accordance with the procedures given in EN 13501-1:2018.

2. Beschreibung zum Bauprodukt / Description of the construction product

Das Produkt wird in den in Punkt 3.1 aufgeführten Prüfberichten, die der Klassifizierung zugrunde liegen, vollständig beschrieben. Dabei wurde das Produkt mit den folgenden Produktparametern getestet.

The product is fully described in the test reports in support of this classification listed in section 3.1. The product was tested adhering to the following product parameters.

"CS Molton, schwarz"	
Gesamtdicke Total thickness	= 0,79 mm
Flächengewicht Weight per unit area	= 342 g/m ²
Farbe Colour	Schwarz black
"CS Molton, weiß"	
Gesamtdicke Total thickness	= 0,76 mm
Flächengewicht Weight per unit area	= 334 g/m ²
Farbe Colour	weiß white

Das Produkt erfüllt nach Angaben des Auftraggebers keine harmonisierte europäische technische Spezifikation (z. B. Produktnorm oder EAD).

According to the applicant, the product is not compliant with any harmonised European technical specification (e.g. product standard or EAD).

3. Prüfberichte und Prüfergebnisse als Grundlage dieser Klassifizierung

Test reports and test results as a basis for this classification

3.1. Prüfberichte / Test reports

Name des Labors Name of laboratory	Auftraggeber Sponsor	Prüfverfahren Test method	Prüfbericht, Datum Test report, date
Prüfinstitut Hoch		EN ISO 11925-2 (Einzelflammentest / single flame source test)	PB-Hoch-260093 26.01.2026
		EN 13823 (SBI)	PB-Hoch-260094 26.01.2026



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: EN13501-1

J&C Joel 
Inspiration in every performance



Prüfinstitut Hoch GmbH

Lerchenweg 1
D-97650 Fladungen

Seite 3 von 5 des Klassifizierungsberichts

page 3 of 5 of classification report

KB-Hoch-260095

3.2. Ergebnisse / Results

Prüfverfahren Test method	Parameter Parameter	Anzahl der Prüfungen Number of tests	Ergebnisse Results	Anforderung für B – s1,d0 Requirements
EN ISO 11925-2	F_s	16 (insg. / total 24)	max. 130 mm	–
	$F_s \leq 150$ mm Flammenausbreitung höchstens 150 mm flame spread no more than 150 mm		ja yes	erfüllt compliant
	Brennendes Abtropfen flaming droplets		nein no	erfüllt compliant
F_s Maximale vertikale Flammenausbreitung [mm]. Maximum vertical flame spread [mm].				
Tabelle / Table 1: Prüfergebnis der Kleinbrennerprüfung / Result of single-flame source test				

Prüfverfahren Test method	Parameter Parameter	Anzahl der Prüfungen Number of tests	Ergebnisse (Mittelwert) Results (average value)	Anforderung Requirement
EN 13823	FIGRA _{0,2MJ}	3 (insg. / total 5)	0 W/s	A2 / B: ≤ 120 W/s
	FIGRA _{0,4MJ}		0 W/s	C: ≤ 250 W/s D: ≤ 750 W/s
	THR _{600s}		0,2 MJ	A2 / B: ≤ 7,5 MJ C: ≤ 15 MJ
	SMOGRA		0 m ² /s ²	s1: ≤ 30 m ² /s ² s2: ≤ 180 m ² /s ²
	TSP _{600s}		23 m ²	s1: ≤ 50 m ² s2: ≤ 200 m ²
	FDP		d0	d0: Kein Brennen / no flaming d1: ≤ 10 s Brenndauer / flaming d2: > 10 s Brenndauer / flaming
	LSF		erfüllt compliant	Rand der Probe nicht erreicht Sample edge not reached
Erläuterungen / remarks:				
FIGRA _{0,2MJ}	Feuerwachstumswert [W/s] nach Erreichen des THR-Schwellenwertes 0,2 MJ Fire Growth Rate [W/s] after reaching a THR threshold of 0,2 MJ			
FIGRA _{0,4MJ}	Feuerwachstumswert [W/s] nach Erreichen des THR-Schwellenwertes 0,4 MJ Fire Growth Rate [W/s] after reaching a THR threshold of 0,4 MJ			
THR _{600s}	Gesamte freigesetzte Wärme während der ersten 600 Sekunden Beflammung [MJ] Total heat release during the first 600 seconds of flame impingement [MJ]			
SMOGRA	Rauchentwicklungsrates [m ² /s ²] Smoke Growth Rate [m ² /s ²]			
TSP _{600s}	gesamte freigesetzte Rauchmenge während der ersten 600 Sekunden Beflammung [m ²] Total smoke production during the first 600 seconds of flame impingement [m ²]			
LSF	seitliche Flammenausbreitung bis zur Außenkante des langen Probenflügels lateral spread of flame, reaching the far edge of the large sample wing			
FDP	brennendes Abtropfen während der ersten 600 Sekunden Beflammung [s] flaming droplets / particles during the first 600 seconds of flame impingement [s]			
Tabelle / Table 2: Prüfergebnisse der SBI-Prüfungen / SBI test results				



United Kingdom



United Arab Emirates



+44 1422 833835



+971 4 884 7801



uksales@jcjoel.com



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: EN13501-1

J&C Joel 
Inspiration in every performance



Prüfinstitut Hoch GmbH
Lerchenweg 1
D-97650 Fladungen

Seite 4 von 5 des Klassifizierungsberichts
page 4 of 5 of classification report
KB-Hoch-260095

4. Klassifizierung und Anwendungsgebiet / Classification and field of application

4.1. Klassifizierung / Classification

Die Klassifizierung ist nach EN 13501-1:2018, Abschnitt 11 (Bauprodukte mit Ausnahme von Bodenbelägen) erfolgt.

This classification has been carried out acc. to EN 13501-1:2018, section 11 (construction products, excluding floorings).

Brandverhalten reaction to fire		Rauchentwicklung smoke production			Brennendes Abtropfen/Abfallen flaming droplets
B	–	s	1	,	d 0

Klassifizierung / Classification: B – s1,d0

4.2. Anwendungsgebiet / Field of application

Die Klassifizierung in Abschnitt 4.1 ist nur für das auf Seite 1 genannte und im Abschnitt 2 sowie den in Abschnitt 3.1 genannten Prüfberichten näher beschriebene Bauprodukt gültig.

Die Klassifizierung ist außerdem für die folgenden Produktparameter gültig:

- Farbe schwarz oder weiß

Diese Klassifizierung gilt für folgende Endanwendungsbedingungen:

- Angrenzende flächige Baustoffe müssen mindestens der Klasse A1 oder A2-s1,d0 nach EN 13501-1 entsprechen und eine Dicke von mindestens 9 mm und eine Rohdichte von mindestens 653 kg/m³ aufweisen. Der Abstand des Produkts zu diesen Baustoffen, muss mindestens 40 mm betragen. Ausgenommen davon sind Untergründe aus Gipsplatten, die nicht in diesem Endanwendungsbereich mitbegriffen sind.

The classification in section 4.1 is valid solely for the product referred to on page 1 and described in detail in section 2 as well as in the test reports listed in section 3.1.

The classification is additionally valid for the following product parameters:

- Colour black or white

This classification is valid for the following end use conditions:

- If fixed in front of underlying materials, these have to be at least of class A1 or A2-s1,d0 (EN 13501-1) and must have a thickness of at least 9 mm and a gross density of no less than 653 kg/m³. The distance of the product to these underlying materials must be at least 40 mm. Gypsum plasterboards are exempt as underlying materials and are not included in this end use condition.



5. Einschränkungen / Limitations

5.1. Geltungsdauer / Duration of validity

Die Klassifizierung gilt bis zum auf Seite 1 angegebenen Datum. Sie kann nach einer Überprüfung des Brandverhaltens verlängert werden. Der Klassifizierungsbericht verliert außerdem seine Gültigkeit, wenn sich die Klassifizierungskriterien gemäß DIN EN 13501-1 ändern oder ergänzt werden, oder wenn die Produktzusammensetzung oder der Produktaufbau geändert werden.



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com

Fire Test Certificate - Specimen

Fabric: IFR Molton CS

Type: EN13501-1

J&C Joel 
Inspiration in every performance



Prüfinstitut Hoch GmbH
Lerchenweg 1
D-97650 Fladungen

Seite 5 von 5 des Klassifizierungsberichts
page 5 of 5 of classification report
KB-Hoch-260095

Wenn keine kontinuierliche Überprüfung des Brandverhaltens durch den Hersteller stattfindet, verliert dieser Klassifizierungsbericht bei jeder Änderung des Produktionsprozesses, des Produktionsumfeldes, der Ausgangsstoffe oder der Zulieferer der Komponenten seine Gültigkeit. Das Brandverhalten muss dann erneut nachgewiesen werden.

This classification remains valid no later than until the date stated on page 1. It can be renewed after re-evaluation of the reaction to fire. This classification also loses its validity as soon as the classification criteria according to DIN EN 13501-1 are altered or amended, or as soon as the product formulation or its composition are altered. If the fire behaviour of the product is not continuously monitored by the manufacturer, each change in either of production process, production environment, raw materials, or chain of suppliers causes this classification to become invalid. In this case, the fire behaviour has to be reassessed.

5.2. Hinweise / Remarks

In Verbindung mit anderen Baustoffen, mit anderen Abständen, Befestigungen, Fugenausbildungen/Verbindungen, Dicken- oder Rohdichtenbereichen, Beschichtungen als in den Abschnitten 2 und 0 angegeben, kann das Brandverhalten negativ beeinflusst werden, so dass die Klassifizierung in Abschnitt 4.1 nicht mehr gilt. Das Brandverhalten von anderen als den oben angegebenen Parametern ist gesondert nachzuweisen.
Used in combination with other materials, esp. other substrates/backings, air gaps/voids, types of fixation joints, thickness or density ranges, coatings than those given in sections 2 and 0, the fire performance is likely to be influenced negatively, so that the classification assigned in section 4.1 will no longer be valid. The fire performance with parameters other than those given above has to be tested and classified separately.

Dieser Klassifizierungsbericht ersetzt nicht einen gegebenenfalls notwendigen baurechtlichen / bauaufsichtlichen Nachweis nach Landesbauordnung
This classification report is in no case a substitute for any required certification according to German building regulations.

Der Klassifizierungsbericht darf ohne vorherige Zustimmung des Prüfinstitut Hoch nur innerhalb des Geltungszeitraumes (siehe Abschnitt 5.1) und nur vollständig und nach Form und Inhalt unverändert veröffentlicht oder vervielfältigt werden.
Without written consent of the test laboratory, this test report may only be published or reproduced during its denoted period of validity (cf. section 5.1), providing that no changes to appearance or content are made and the report is complete.

Dieses Dokument stellt keine Typzulassung oder Zertifizierung des Produktes dar.
This document does not represent type approval or certification of the product.

Fladungen, 26.01.2026

Sachbearbeiterin
Clerk in charge


(M. Eng. Susanne Hart)



Leiter der Prüfstelle
Head of test laboratory


(Dipl.-Ing.(FH) Andreas Hoch)



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com



United Kingdom



+44 1422 833835



uksales@jcjoel.com



United Arab Emirates



+971 4 884 7801



menasales@jcjoel.com

www.jcjoel.com