



At a Glance

J&C Joel offer a range of pulleys designed for use with flying systems. We offer various WLL capacities and lines per pulley. Standard sizes are shown below. Custom options are available upon request.

Features

- Suitable for manual or motorised systems
- Dual ball bearings to assure smooth operation
- Pulleys manufactured from black polyamide
- Steel side plate and frame
- WLL of upto 1000kg available on request
- Standard and custom mounting brackets available
- CE Marked

Mounting & Girder Dogs

We have a range of solutions to clamp each pulley block onto an I beam. Our standard fixes to beams with a flange width between 41 - 207mm and a flange thickness of 10mm, with a safe working load of 250kg. Custom brackets are available on request.

For our full Winch Brochure, [click download or scan the QR code.](#)



[Download](#)

Pulley ID	WLL (kg)	Pulley Ø (mm)	Rope Ø (mm)	No. Lines	Dim. X (mm)	Dim. Y (mm)	Dim. Z (mm)	Dim. A (mm)	Self Weight (kg)	Plate Thickness
JCJ-PU-100-1	125	100	4	1	36	142	150	80	1.60	4
JCJ-PU-100-2	125	100	4	2	36	142	150	80	1.60	4
JCJ-PU-100-3	125	100	4	3	45	142	150	80	1.70	4
JCJ-PU-100-4	125	100	4	4	53	142	150	80	1.85	4
JCJ-PU-100-5	125	100	4	5	62	142	150	80	1.95	4
JCJ-PU-100-6	125	100	4	6	70	142	150	80	2.15	4
JCJ-PU-150-1	250	150	6	1	36	167	200	80	2.40	4
JCJ-PU-150-2	250	150	6	2	42	167	200	80	2.55	4
JCJ-PU-150-3	250	150	6	3	54	167	200	80	2.85	4
JCJ-PU-150-4	250	150	6	4	66	167	200	80	3.40	4
JCJ-PU-150-5	250	150	6	5	78	167	200	80	3.80	4
JCJ-PU-150-6	250	150	6	6	90	167	200	80	4.10	4
JCJ-PU-150-1-500	500	150	6	1	40	172	205	80	3.95	6
JCJ-PU-150-2-500	500	150	6	2	46	172	205	80	3.95	6
JCJ-PU-150-3-500	500	150	6	3	58	172	205	80	4.00	6
JCJ-PU-150-4-500	500	150	6	4	70	172	205	80	4.40	6
JCJ-PU-150-5-500	500	150	6	5	82	172	205	80	4.90	6
JCJ-PU-150-6-500	500	150	6	6	94	172	205	80	5.45	6